

# SPOTO CCNP ENCOR 350-401 Free Demo

# **QUESTION 1**

Which LISP device is responsible for publishing EID-to-RLOC mappings for a site?

A. ITR

B. ETR

C. MR

D. MS

## Correct Answer: B

**QUESTION 2** In a Cisco SD-WAN solution, how is the health of a data plane tunnel monitored?

A. with IP SLA



*Website: <u>https://cciedump.spoto.net/</u><u>https://spotodumps.com</u> <i>WhatsApp:+86-18344981205 support@spoto.net* 



- B. ARP probing
- C. using BFD
- D. with OMP

# Correct Answer: C

## **QUESTION 3**

An engineer must protect their company against ransomware attacks. Which solution allows the engineer to block the execution stage and prevent file encryption?

- A. Use Cisco AMP deployment with the Malicious Activity Protection engine enabled.
- B. Use Cisco AMP deployment with the Exploit Prevention engine enabled.
- C. Use Cisco Firepower and block traffic to TOR networks.
- D. Use Cisco Firepower with Intrusion Policy and snort rules blocking SMB exploitation.

## Correct Answer: A

# **QUESTION 4**

Why would an engineer use YANG?

- A. to access data using SNMP
- B. to translate JSON into an equivalent XML syntax
- C. to transport data between a controller and a network device
- D. to model data for NETCONF



*Website: <u>https://cciedump.spoto.net/</u><u>https://spotodumps.com</u> <i>WhatsApp:+86-18344981205 support@spoto.net* 



Correct Answer: D



*Website: <u>https://cciedump.spoto.net/ https://spotodumps.com</u> <i>WhatsApp:+86-18344981205 support@spoto.net* 



# **QUESTION 5**

Which solution do IaaS service providers use to extend a Layer 2 segment across a Layer 3 network?

- A. VLAN
- B. VTEP
- C. VXLAN
- D. VRF

## Correct Answer: C

#### **QUESTION 6**

An engineer is configuring a new SSID to present users with a splash page for authentication. Which WLAN Layer 3 setting must be configured to provide this functionality?

- A. Web Policy
- B. WPA2 Policy
- C. Local Policy
- D. CCKM

Correct Answer: A



*Website: <u>https://cciedump.spoto.net/ https://spotodumps.com</u> <i>WhatsApp:+86-18344981205 support@spoto.net* 



## **QUESTION 7**

Which measure is used by an NTP server to indicate its closeness to the authoritative time source?

- A. Latency
- B. hop count
- C. time zone
- D. stratum

# Correct Answer: D

#### **QUESTION 8**

An engineer must create a new SSID on a Cisco 9800 wireless LAN controller. The client has asked to use a pre-shared key for authentication. Which profile must the engineer edit to achieve this requirement?

- A. RF
- B. Flex
- C. WLAN
- D. Policy

## Correct Answer: C

## **QUESTION 9**

A customer wants to use a single SSID to authenticate IoT devices using different passwords. Which Layer 2 security type must be configured in conjunction with Cisco ISE to achieve this requirement?



Website: <u>https://cciedump.spoto.net/ https://spotodumps.com</u> WhatsApp:+86-18344981205 support@spoto.net



- A. Fast Transition
- B. Cisco Centralized Key Management
- C. Identity PSK
- D. Central Web Authentication

# Correct Answer: C

# **QUESTION 10**

What is the recommended MTU size for a Cisco SD-Access Fabric?

A. 1500

B. 17914

C. 9100

D. 4464

Correct Answer: C



*Website: <u>https://cciedump.spoto.net/ https://spotodumps.com</u> <i>WhatsApp:+86-18344981205 support@spoto.net*